



## Thermal Receipt Printer

# XP-Q200H/Q260H

- Low noise, high speed printing
- 80mm paper bin capacity
- Kitchen and network printing are available
- Call reminder and error alarm
- Printer head over-temperature protection
- Support QR code & PDF 417
- IAP on line upgrade



## XP-Q200H/Q260H

### Thermal Receipt Printer



Model	XP-Q200H	XP-Q260H
Printing method	Direct thermal	
Printing speed	230 mm/s	260 mm/s
Paper width	79.5±0.5mm	
Paper thickness	0.06~0.08mm	
Column capacity	576 dots/line or 512 dots/line	
Interface	USB+Serial / USB+Lan	USB+Serial+Lan
Line spacing	3.75mm (Adjustable by commands)	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese: 3.0×3.0mm(24×24 dots)	
<b>Barcode Character</b>		
Extension character sheet	PC437(Std.Europe) / (Katakana) / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / (West Europe) / (Greek) / (Hebrew) / (East Europe) / (Iran) / (WPC1252) / PC866(Cyrillic#2) / PC852(Latin2) / (PC858) / (IranII) / (Latvian) / (Arabic) / (PT1511251)	
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	256 Kbytes	
NV Flash	256 Kbytes	
<b>Power</b>		
Power adaptor Input	AC 100~240V, 50~60Hz	
Printer Input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
<b>Physical characteristics</b>		
Weight	1.0 Kg	
Dimensions	180*139*131mm	
<b>Environmental Requirements</b>		
Work environment	Temperature (0~45℃), humidity(10~80%)	
Storage environment	Temperature(-10~60℃), humidity(10~90%)	
<b>Reliability</b>		
Auto cutter	Partial	
Cutter life	1.5 million cuts	
Printer head life	150Km	
<b>Software</b>		
Emulation	ESC/POS	
Driver	Windows / Linux	
Utility	Windows & Linux test Utility	

